



TIMKEN FORGE OF AMERICA BEARING CORP.



E-PF-TRB-125MM Bearing 2D drawings and 3D CAD models

TIMKEN E-PF-TRB-125MM Flange Block Bearings

Bearing No. E-PF-TRB-125MM

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	59.02
EAN	0053893778907
Product Group	M06288
Number of Mounting Holes	6
Mounting Method	Concentric Collar
Housing Style	6 Bolt Round Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	7/8 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch - Metric	Metric
Long Description	6 Bolt Round Flange Block; 125MM Bore; 325.1MM Bolt Circle; 161.925MM Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Tapered Roller Bearing; 184.15MM Length Thru Bore; Relubricatable
Other Features	Double Row Wide Inner



TIMKEN FORGE OF AMERICA BEARING CORP.

	Race With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	E-PF-TRB-125MM
Weight / LBS	130
Nominal Bolt Circle Diameter Round	12.8 Inch 325.1 Millimeter
Cartridge Pilot Diameter	11 Inch 279.4 Millimeter
d	4.921 Inch 125 Millimeter
Cartridge Pilot Depth	3.188 Inch 80.975 Millimeter
D	7.25 Inch 184.15 Millimeter
Bolt Spacing	6.375 Inch 161.925 Millimeter
Shaft Size	4.921 in
Shaft Size Type	Metric
Weight	130.000 lb
UPC Code	053893778907
Dimension B	7-1/4 in
Dimension H	14-3/4 in
Dimension A	5-1/16 in
Dimension N ₂	6.375 in
Dimension J	12-3/4 in
Dimension A ₃	1-3/4 in
Bolt Diameter	7/8 in
Dimension E	2-31/32 in
Dimension A ₁	1-1/4 in
Dimension D ¹	11 in



TIMKEN FORGE OF AMERICA BEARING CORP.

Dimension d_1	7-3/4 in
Dimension A_2	1-7/8 in
e	0.47
X (if $F_a/F_r \leq e$)	0.87
Y (if $F_a/F_r \leq e$)	1.83
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.21
K Factor	1.27
C_{90} Dynamic Load Rating ²	45500 lb
C_0 Static Load Rating	266000 lb
F_{a-max} Maximum Permissible Thrust Load ³	6908 lb
F_{r-max} Maximum Allowable Slip Fit Radial Load ⁴	35000 lb
Max. Speed ⁵	1200 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur